Printing date 17.04.2024

×

Version number 1

Revision: 16.04.2024



(Contd. on page 2)

Printing date 17.04.2024

Version number 1

Revision: 16.04.2024

	(Con	ntd. of page
Signal word Da		or page
Hazard-determ	ining components of labelling:	
acetone		
n-butyl acetate		
2-methoxy-1-me	ethylethyl acetate	
Hazard stateme		
	y flammable aerosol.	
	ed container: May burst if heated.	
H319 Causes se	erious eye irritation.	
H336 May caus	se drowsiness or dizziness.	
Precautionary s	statements	
P101	If medical advice is needed, have product container or label at hand.	
P102	Keep out of reach of children.	
P103	Read carefully and follow all instructions.	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition so smoking.	ources. I
P211	Do not spray on an open flame or other ignition source.	
P251	Do not pierce or burn, even after use.	
P271	Use only outdoors or in a well-ventilated area.	
P305+P351+P.	338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contac	ct lenses,
	present and easy to do. Continue rinsing.	
P312	Call a POISON CENTER/doctor if you feel unwell.	
P337+P313	If eye irritation persists: Get medical advice/attention.	
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.	
P501	Dispose of contents/container in accordance with local/regional/national/intregulations.	ternation
Additional info	rmation:	
	te ventilation, explosive atmosphere/gas mix may be created.	
	rdous respirable droplets may be formed when sprayed. Do not breathe spray or mi	st

• *PBT:* Not applicable. • *vPvB:* Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

*

• Description: Mixture of substances listed below with nonhazardous additions.

• Dangerous components:		
CAS: 67-64-1	acetone	25-<50%
EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-xxxx	♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	
CAS: 74-98-6	propane	10-<25%
EINECS: 200-827-9	🚸 Flam. Gas 1A, H220; Press. Gas (Comp.), H280, EUH018	
Reg.nr.: 01-2119486944-21-xxxx		
CAS: 106-97-8	butane (containing $\leq 0,1$ % butadiene (203-450-8))	5-<10%
EINECS: 203-448-7	🛞 Flam. Gas 1A, H220; Press. Gas (Comp.), H280, EUH018	
Reg.nr.: 01-2119474691-32-xxxx		
CAS: 123-86-4	n-butyl acetate	5-<10%
EINECS: 204-658-1	🛞 Flam. Liq. 3, H226; 🚺 STOT SE 3, H336, EUH066	
Reg.nr.: 01-2119485493-29-xxxx		
	(Con	ntd. on page 3)

Printing date 17.04.2024

Version number 1

Revision: 16.04.2024

Trade name: Aerosol SOLL Backlight black

CAS: 9004-70-0	nitrocellulose with water(not less than 25% water, by mass)	ntd. of page 2 5-<10%
Reg.nr.: no Reach No. availlable	🤣 Expl. 1.1, H201	
CAS: 75-28-5	isobutane (containing $\leq 0,1$ % butadiene (203-450-8))	5-<10%
EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	🚸 Flam. Gas 1A, H220; Press. Gas (Comp.), H280, EUH018	
CAS: 108-65-6	2-methoxy-1-methylethyl acetate	2.5-<5%
EINECS: 203-603-9 Reg.nr.: 01-2119475791-29-xxxx	🚸 Flam. Liq. 3, H226; 🚸 STOT SE 3, H336	
CAS: 64-17-5	ethanol	2.5-<5%
EINECS: 200-578-6	🚸 Flam. Liq. 2, H225; 🚺 Eye Irrit. 2, H319	
Reg.nr.: 01-2119457610-43-xxxx	· · · ·	
CAS: 1330-20-7	xylene, mixture of isomers	1-<2.5%
EINECS: 215-535-7	Flam. Liq. 3, H226; 🚸 STOT RE 2, H373; Asp. Tox. 1,	
Reg.nr.: 01-2119488216-32-xxxx	H304; ۯ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit.	
	2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	
CAS: 7397-62-8	butyl glycollate	1-<2.5%
EINECS: 230-991-7	🚸 Repr. 2, H361; 🛟 Eye Dam. 1, H318	
Reg.nr.: 01-2119514685-36-xxxx		
CAS: 71-36-3	butan-1-ol	<1%
EINECS: 200-751-6	🚸 Flam. Liq. 3, H226; 🔗 Eye Dam. 1, H318; 🕔 Acute Tox.	
Reg.nr.: 01-2119484630-38-xxxx	4, H302; Skin Irrit. 2, H315; STOT SE 3, H335; STOT SE 3,	
	H336	
CAS: 100-41-4 ethylbenzene		<1%
EINECS: 202-849-4	🚸 Flam. Liq. 2, H225; 🚸 STOT RE 2, H373; Asp. Tox. 1,	
Reg.nr.: 01-2119489370-35-xxxx	H304; 🚯 Acute Tox. 4, H332	

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

• After inhalation: Supply fresh air; consult doctor in case of complaints.

• After skin contact: Generally the product does not irritate the skin.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

• After swallowing: If symptoms persist consult doctor.

• 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

 \cdot 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media -

· Suitable extinguishing agents: Cool container whit water

• 5.2 Special hazards arising from the substance or mixture No further relevant information available.

• 5.3 Advice for firefighters

· Protective equipment: No special measures required.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)

GB

Printing date 17.04.2024

Version number 1

Revision: 16.04.2024

Trade name: Aerosol SOLL Backlight black

(Contd. of page 3)

 \cdot **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

• 6.3 Methods and material for containment and cleaning up: Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.

• **6.4 Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight. Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, *i.e. electric lights. Do not pierce or burn, even after use.*

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

• **Requirements to be met by storerooms and receptacles:** Observe official regulations on storing packagings with pressurised containers.

• Information about storage in one common storage facility: Not required.

- Further information about storage conditions: None.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

•	8.1	Control	parameters
---	-----	---------	------------

-	lients with limit values that require monitoring at the workplace:	
67-64-	1 acetone	
	Short-term value: 3620 mg/m³, 1500 ppm	
i i	Long-term value: 1210 mg/m³, 500 ppm	
106-97	7-8 butane (containing ≤0,1 % butadiene (203-450-8))	
WEL 3	Short-term value: 1810 mg/m³, 750 ppm	
i i	Long-term value: 1450 mg/m³, 600 ppm	
	Carc (if more than 0.1% of buta-1.3-diene)	
123-86	6-4 n-butyl acetate	
WEL 3	Short-term value: 966 mg/m³, 200 ppm	
i i	Long-term value: 724 mg/m³, 150 ppm	
108-65	5-6 2-methoxy-1-methylethyl acetate	
WEL S	Short-term value: 548 mg/m³, 100 ppm	
j. j	Long-term value: 274 mg/m³, 50 ppm	
L.	Sk	
64-17-	5 ethanol	
WEL I	Long-term value: 1920 mg/m³, 1000 ppm	
1330-2	20-7 xylene, mixture of isomers	
WEL S	Short-term value: 441 mg/m³, 100 ppm	
i i	Long-term value: 220 mg/m³, 50 ppm	
1	Sk; BMGV	
		(Contd. on page

Printing date 17.04.2024

Version number 1

Revision: 16.04.2024

(Contd. of page 4)

Trade name: Aerosol SOLL Backlight black

71-36-3 butan-1-ol WEL Short-term value: 154 mg/m³, 50 ppm

100-41-4 ethylbenzene

Sk

WEL Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm Sk

· Ingredients with biological limit values:

1330-20-7 xylene, mixture of isomers

BMGV 650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

• Appropriate engineering controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

• General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:



When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Half mask with combination filter, class A1P2 minimum, or breathing mask with outer air supply.

· Hand protection

Protective gloves



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Penetration time of glove material

Gloves must be changed after every contamination.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- \cdot For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:
- butyl rubber, 0,7mm • Eye/face protection

Safety glasses



Tightly sealed goggles

(Contd. on page 6)

Printing date 17.04.2024

Version number 1

Revision: 16.04.2024

Trade name: Aerosol SOLL Backlight black

(Contd. of page 5)

01 Information of the total total total	
9.1 Information on basic physical and chemical p General Information	roperties
Physical state	Aerosol
Colour:	
	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling	11590
range	-44.5 °C
Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	1.7 Vol %
Upper:	13 Vol %
Flash point:	<0 °C
Auto-ignition temperature:	$365 \ ^{\circ}C \ (106-97-8 \ butane \ (containing \le 0,1 \ \% \ butane \ (203-450-8)))$
Decomposition temperature:	Not determined.
pH	Not determined.
Viscosity:	
Kinematic viscosity	Not determined.
Dynamic:	Not determined.
Solubility	
water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure at 20 °C:	3,600 hPa
Vapour pressure at 50 °C:	800 hPa
Density and/or relative density	
Relative density	0.78 g/ml
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Aerosol
Important information on protection of health and	
environment, and on safety.	u
	Product is not solficiting
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation
	explosive air/vapour mixtures are possible.
	Not determined.
Solvent content:	
Organic solvents:	87.8 %
	With propellant gas. Content given by weight.
VOC (EU)	(<840g/l)
	87.80 %
Solids content:	5.5 %
Change in condition	
Evaporation rate	Not applicable.
Information with regard to physical hazard classe	8
Explosives	Void
Flammable gases	Void
Aerosols	Extremely flammable aerosol. Pressurised contai
AU03003	May burst if heated.
Ovidising agess	Nay bursi ij nealea. Void
Oxidising gases Gases under pressure	Void Void

GB

Printing date 17.04.2024

Version number 1

Revision: 16.04.2024

Trade name: Aerosol SOLL Backlight black

		(Contd. of page 6
· Flammable liquids	Void	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit flamm	able	
gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
· Desensitised explosives	Void	

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- $\cdot \ \textit{10.5 Incompatible materials:} No further relevant information available.$
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Dermal LD50 110,287 mg/kg (rabbit)

Inhalative LC50/4 h 607 mg/l (rat)

- · Serious eye damage/irritation Causes serious eye irritation.
- · STOT-single exposure May cause drowsiness or dizziness.

· 11.2 Information on other hazards

· Endocrine disrupting properties

541-02-6 2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane

556-67-2 octamethylcyclotetrasiloxane

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- **vPvB:** Ikke relevant.

• 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.

(Contd. on page 8)

List II

List II; III

Printing date 17.04.2024

Version number 1

Revision: 16.04.2024

Trade name: Aerosol SOLL Backlight black

(Contd. of page 7)

· 12.7 Other adverse effects

· Additional ecological information:

· General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

*

2

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

• *Recommendation:* Disposal must be made according to official regulations.

• 14.1 UN number or ID number • ADR, IMDG, IATA	UN1950
14.2 UN proper shipping name	
ADR	1950 AEROSOLS
·IMDG	AEROSOLS
· IATA	AEROSOLS, flammable
· 14.3 Transport hazard class(es)	
ADR	
\mathbf{V}	
· Class	2 5F Gases.
· Label	2.1
· IMDG, IATA	
• Class	2.1 Gases.
· Label	2.1 Guses. 2.1
· 14.4 Packing group · ADR, IMDG, IATA	Void
	not classified
	noi crassifica
14.5 Environmental hazards:	17
Marine pollutant:	No
14.6 Special precautions for user	Warning: Gases.
Hazard identification number (Kemler code):	-
	not classified
EMS Number:	F- D , S - U

Revision: 16.04.2024

Printing date 17.04.2024 Version number 1 Trade name: Aerosol SOLL Backlight black (Contd. of page 8) SW1 Protected from sources of heat. · Stowage Code SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 · Segregation Code litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. · 14.7 Maritime transport in bulk according to IMO Not applicable. instruments · Transport/Additional information: · ADR · Limited quantities (LQ) lLCode: E0 • Excepted quantities (EQ) Not permitted as Excepted Quantity · Transport category 2 · Tunnel restriction code D · IMDG

lL· Limited quantities (LQ) Code: E0 • Excepted quantities (EQ) Not permitted as Excepted Quantity · UN "Model Regulation": UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture VOC: <840g/l

· Poisons Act

- · Regulated explosives precursors
- None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

67-64-1 acetone

· Reportable poisons

None of the ingredients is listed.

· Seveso category P3a FLAMMABLE AEROSOLS

 \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

 \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

(Contd. on page 10)

Listed

[·] Directive 2012/18/EU

[·] Named dangerous substances - ANNEX I None of the ingredients is listed.

GB

Printing date 17.04.2024

Version number 1

Revision: 16.04.2024

Trade name: Aerosol SOLL Backlight black

(Contd. of page 9)

· National regulations:

· Technical instructions (air):

 Class
 Share in %

 NK
 50-100

· Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H201 Explosive; mass explosion hazard.
- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H361 Suspected of damaging fertility or the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.
- EUH018 In use may form flammable/explosive vapour-air mixture.
- EUH066 Repeated exposure may cause skin dryness or cracking.

· Department issuing SDS: Product safety department

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- ATE: Acute toxicity estimate values Expl. 1.1: Explosives – Division 1.1
- Flam. Gas 1A: Flammable gases Category 1A
- Aerosol 1: Aerosols Category 1
- : Aerosols Category 3
- Press. Gas (Comp.): Gases under pressure Compressed gas
- Flam. Liq. 2: Flammable liquids Category 2
- Flam. Liq. 3: Flammable liquids Category 3
- Acute Tox. 4: Acute toxicity Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Dam. 1: Serious eye damage/eye irritation Category 2

Printing date 17.04.2024

Version number 1

Revision: 16.04.2024

Trade name: Aerosol SOLL Backlight black

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (single exposure) – Category 5 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1 • * Data compared to the previous version altered.

(Contd. of page 10)

GB