Version number 1 Revision: 17.04.2024 Printing date 17.04.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: Aerosol SOLL Spray putty

· (Article number) product ID.: S700023

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Application of the substance / the mixture: painting

· Uses advised against No further relevant information available.

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

UAB "HELVINA"

Parko str. 96

LT-54464 Ramu iai

Kaunas distr., Lithuania

Tel: +370 37 308 901 Fax: +370 37 308 902 info@helvina.lt www.helvina.lt

· Further information obtainable from: Product safety department

• 1.4 Emergency telephone number: Tel: +370 5 236 2052 / +370 687 53378

· national:

National Poisons Information Service, Birmingham

Tel.: 844 892 0111

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Aerosol 1 H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.



Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms





GHS02

GHS07

Printing date 17.04.2024 Version number 1 Revision: 17.04.2024

Trade name: Aerosol SOLL Spray putty

(Contd. of page 1)

· Signal word Danger

· Hazard-determining components of labelling:

acetone

n-butyl acetate

2-methoxy-1-methylethyl acetate

ethyl acetate

· Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P271 Use only outdoors or in a well-ventilated area.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell. P337+P313 If eye irritation persists: Get medical advice/attention.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

Without adequate ventilation, explosive atmosphere/gas mix may be created.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- \cdot **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- Description: Mixture of substances listed below with nonhazardous additions.

	· Dangerous components:		
	CAS: 67-64-1	acetone	25-<50%
	EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-xxxx	♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	
	CAS: 74-98-6	propane	10-<25%
	EINECS: 200-827-9	🅸 Flam. Gas 1A, H220; Press. Gas (Comp.), H280, EUH018	
L	Reg.nr.: 01-2119486944-21-xxxx		
	CAS: 106-97-8	butane (containing ≤ 0.1 % butadiene (203-450-8))	5-<10%
	EINECS: 203-448-7	🕸 Flam. Gas 1A, H220; Press. Gas (Comp.), H280, EUH018	
	Reg.nr.: 01-2119474691-32-xxxx		
	CAS: 123-86-4	n-butyl acetate	5-<10%
	EINECS: 204-658-1	🚸 Flam. Liq. 3, H226; 아 STOT SE 3, H336, EUH066	
	Reg.nr.: 01-2119485493-29-xxxx		
		(Cor	atd on page 3)

(Contd. on page 3)

Printing date 17.04.2024 Version number 1 Revision: 17.04.2024

Trade name: Aerosol SOLL Spray putty

CAS: 75-28-5	isobutane (containing ≤ 0.1 % butadiene (203-450-8))	5-<10
EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	🏇 Flam. Gas 1A, H220; Press. Gas (Comp.), H280, EUH018	
CAS: 9004-70-0 Reg.nr.: no Reach No. availlable	nitrocellulose with water(not less than 25% water, by mass) Expl. 1.1, H201	2.5-<.
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29-xxxx	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	2.5-<.
CAS: 141-78-6 EINECS: 205-500-4 Reg.nr.: 01-2119475103-46-xxxx	ethyl acetate Flam. Liq. 2, H225;	2.5-<.
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-xxxx	xylene, mixture of isomers Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	2.5-<.
CAS: 64-17-5 EINECS: 200-578-6 Reg.nr.: 01-2119457610-43-xxxx	ethanol Flam. Liq. 2, H225; Eye Irrit. 2, H319	1-<2
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35-xxxx	ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332	<19
CAS: 7397-62-8 EINECS: 230-991-7 Reg.nr.: 01-2119514685-36-xxxx	butyl glycollate ♦ Repr. 2, H361; ♦ Eye Dam. 1, H318	<19
CAS: 71-36-3 EINECS: 200-751-6 Reg.nr.: 01-2119484630-38-xxxx	butan-1-ol ♠ Flam. Liq. 3, H226; ♠ Eye Dam. 1, H318; ♠ Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335; STOT SE 3, H336	<19

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media -
- · Suitable extinguishing agents: Cool container whit water
- · 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

GE

Printing date 17.04.2024 Version number 1 Revision: 17.04.2024

Trade name: Aerosol SOLL Spray putty

(Contd. of page 3)

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- \cdot 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:	
67-64-1 acetone	

Long-term value: 1210 mg/m^3 , 500 ppm $106-97-8 \text{ butane (containing } \le 0.1 \% \text{ butadiene (203-450-8))}$

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm

Carc (if more than 0.1% of buta-1.3-diene)

WEL Short-term value: 3620 mg/m³, 1500 ppm

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm

Sk

(Contd. on page 5)

Printing date 17.04.2024 Version number 1 Revision: 17.04.2024

Trade name: Aerosol SOLL Spray putty

141-78-6 ethyl acetate		(Contd. of page
Long-term value: 734 mg/m³, 200 ppm 1330-20-7 xylene, mixture of isomers WEL	141-78	-6 ethyl acetate
1330-20-7 xylene, mixture of isomers WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV 64-17-5 ethanol WEL Long-term value: 1920 mg/m³, 1000 ppm 100-41-4 ethylbenzene WEL Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm Sk 71-36-3 butan-1-ol WEL Short-term value: 154 mg/m³, 50 ppm Sk Ingredients with biological limit values: 1330-20-7 xylene, mixture of isomers BMGV 650 mmol/mol creatinine Medium: urine Sampling time: post shift	WEL S	hort-term value: 1468 mg/m³, 400 ppm
WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV 64-17-5 ethanol WEL Long-term value: 1920 mg/m³, 1000 ppm 100-41-4 ethylbenzene WEL Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm Sk 71-36-3 butan-1-ol WEL Short-term value: 154 mg/m³, 50 ppm Sk Ingredients with biological limit values: 1330-20-7 xylene, mixture of isomers BMGV 650 mmol/mol creatinine Medium: urine Sampling time: post shift	L	ong-term value: 734 mg/m³, 200 ppm
Long-term value: 220 mg/m³, 50 ppm Sk; BMGV 64-17-5 ethanol WEL Long-term value: 1920 mg/m³, 1000 ppm 100-41-4 ethylbenzene WEL Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm Sk 71-36-3 butan-1-ol WEL Short-term value: 154 mg/m³, 50 ppm Sk Ingredients with biological limit values: 1330-20-7 xylene, mixture of isomers BMGV 650 mmol/mol creatinine Medium: urine Sampling time: post shift	1330-2	0-7 xylene, mixture of isomers
Sk; BMGV	WEL S	hort-term value: 441 mg/m³, 100 ppm
64-17-5 ethanol WEL Long-term value: 1920 mg/m³, 1000 ppm 100-41-4 ethylbenzene WEL Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm Sk 71-36-3 butan-1-ol WEL Short-term value: 154 mg/m³, 50 ppm Sk Ingredients with biological limit values: 1330-20-7 xylene, mixture of isomers BMGV 650 mmol/mol creatinine Medium: urine Sampling time: post shift	L	ong-term value: 220 mg/m³, 50 ppm
WEL Long-term value: 1920 mg/m³, 1000 ppm 100-41-4 ethylbenzene WEL Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm Sk 71-36-3 butan-1-ol WEL Short-term value: 154 mg/m³, 50 ppm Sk Ingredients with biological limit values: 1330-20-7 xylene, mixture of isomers BMGV 650 mmol/mol creatinine Medium: urine Sampling time: post shift	S	'k; BMGV
### Too-41-4 ethylbenzene WEL Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm Sk 71-36-3 butan-1-ol WEL Short-term value: 154 mg/m³, 50 ppm Sk Ingredients with biological limit values: 1330-20-7 xylene, mixture of isomers BMGV 650 mmol/mol creatinine Medium: urine Sampling time: post shift	64-17-5	5 ethanol
WEL Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm Sk 71-36-3 butan-1-ol WEL Short-term value: 154 mg/m³, 50 ppm Sk Ingredients with biological limit values: 1330-20-7 xylene, mixture of isomers BMGV 650 mmol/mol creatinine Medium: urine Sampling time: post shift	WEL L	ong-term value: 1920 mg/m³, 1000 ppm
Long-term value: 441 mg/m³, 100 ppm Sk 71-36-3 butan-1-ol WEL Short-term value: 154 mg/m³, 50 ppm Sk Ingredients with biological limit values: 1330-20-7 xylene, mixture of isomers BMGV 650 mmol/mol creatinine Medium: urine Sampling time: post shift	100-41	-4 ethylbenzene
Sk	WEL S	hort-term value: 552 mg/m³, 125 ppm
71-36-3 butan-1-ol WEL Short-term value: 154 mg/m³, 50 ppm Sk Ingredients with biological limit values: 1330-20-7 xylene, mixture of isomers BMGV 650 mmol/mol creatinine Medium: urine Sampling time: post shift	L	ong-term value: 441 mg/m³, 100 ppm
WEL Short-term value: 154 mg/m³, 50 ppm Sk Ingredients with biological limit values: 1330-20-7 xylene, mixture of isomers BMGV 650 mmol/mol creatinine Medium: urine Sampling time: post shift	S	k
Ingredients with biological limit values: 1330-20-7 xylene, mixture of isomers BMGV 650 mmol/mol creatinine Medium: urine Sampling time: post shift	71-36-3	3 butan-1-ol
Ingredients with biological limit values: 1330-20-7 xylene, mixture of isomers BMGV 650 mmol/mol creatinine Medium: urine Sampling time: post shift	WEL S	hort-term value: 154 mg/m³, 50 ppm
1330-20-7 xylene, mixture of isomers BMGV 650 mmol/mol creatinine Medium: urine Sampling time: post shift	S	k
BMGV 650 mmol/mol creatinine Medium: urine Sampling time: post shift	Ingredi	ients with biological limit values:
Medium: urine Sampling time: post shift	1330-2	0-7 xylene, mixture of isomers
Sampling time: post shift	BMGV	650 mmol/mol creatinine
		Medium: urine
Parameter: methyl hippuric acid		Sampling time: post shift
		Parameter: methyl hippuric acid

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:



When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Half mask with combination filter, class A1P2 minimum, or breathing mask with outer air supply.

$\cdot \textit{ Hand protection }$

Protective gloves



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Penetration time of glove material

Gloves must be changed after every contamination.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

Printing date 17.04.2024 Version number 1 Revision: 17.04.2024

Trade name: Aerosol SOLL Spray putty

(Contd. of page 5)

· For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

butyl rubber, 0,7mm · Eye/face protection Safety glasses



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Aeroso

· Colour: According to product specification

Odour: Characteristic
Odour threshold: Not determined.
Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling

range -44 °C

· Flammability Not applicable.

· Lower and upper explosion limit

· Lower: 1.7 Vol % (74-98-6 propane) *· Upper:* 13 Vol % (67-64-1 acetone)

· Flash point: <0 °C

• Auto-ignition temperature: 365 °C (106-97-8 butane (containing \leq 0,1 % butadiene

(203-450-8)))

Decomposition temperature: Not determined.pH Not determined.

· Viscosity:

Kinematic viscosity
Dynamic:
Not determined.
Not determined.

· Solubility

• water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value) Not determined.

• *Vapour pressure at 20 °C*: 3,600 hPa (74-98-6 propane)

· Vapour pressure at 50 °C: 800 hPa

· Density and/or relative density

Relative density
 Vapour density
 Not determined.

· 9.2 Other information

· Appearance:

· Form: Aerosol

· Important information on protection of health and environment, and on safety.

• **Ignition temperature:** Product is not selfigniting.

Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

Not determined.

(Contd. on page 7)

Printing date 17.04.2024 Version number 1 Revision: 17.04.2024

Trade name: Aerosol SOLL Spray putty

(Contd. of page 6)

· Solvent	content:
-----------	----------

· Organic solvents: 80.8 %

With propellant gas. Content given by weight.

 $\cdot VOC (EU) \qquad (\langle 840g/l \rangle$

80.83 %

· Solids content: 15.4 %

· Change in condition

· Evaporation rate Not applicable.

· Information with regard to physical hazard classes

Explosives VoidFlammable gases Void

· Aerosols Extremely flammable aerosol. Pressurised container:

May burst if heated.

· Oxidising gases Void · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in contact with water Void Void

gases in contact with water Void
Oxidising liquids Void
Oxidising solids Void
Organic peroxides Void
Corrosive to metals Void
Desensitised explosives Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 value	s relevant for	classification:
-----------------	----------------	-----------------

ATE (Acute Toxicity Estimates)

Dermal LD50 61,726 mg/kg (rabbit)
Inhalative LC50/4 h 339 mg/l (rat)

- · Serious eye damage/irritation Causes serious eye irritation.
- · STOT-single exposure May cause drowsiness or dizziness.

(Contd. on page 8)

Printing date 17.04.2024 Version number 1 Revision: 17.04.2024

Trade name: Aerosol SOLL Spray putty

(Contd. of page 7)

- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Ikke relevant.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

CECTION	T 1 4 70		
	14: Transp	ort intori	mation

· 14.1	UN	numbei	or ID	number
--------	----	--------	-------	--------

· ADR, IMDG, IATA UN1950

· 14.2 UN proper shipping name

· ADR 1950 AEROSOLS · IMDG AEROSOLS

· IATA AEROSOLS, flammable

- · 14.3 Transport hazard class(es)
- $\cdot ADR$



· Class 2 5F Gases.

• *Label* 2.1

(Contd. on page 9)

Printing date 17.04.2024 Version number 1 Revision: 17.04.2024

Trade name: Aerosol SOLL Spray putty

	(Contd. of page
· IMDG, IATA	
*	
· Class	2.1 Gases.
· Label	2.1
· 14.4 Packing group	
· ADR, IMDG, IATA	Void
	not classified
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Gases.
· Hazard identification number (Kemler code):	-
	not classified
· EMS Number:	F-D,S-U
· Stowage Code	SWI Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capacity of
	litre: Category A. For AEROSOLS with a capacity abo
	1 litre: Category B. For WASTE AEROSOLS: Catego
Commention Code	C, Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of litre:
	Segregation as for class 9. Stow "separated from" class
	except for division 1.4.
	For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of class
	For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class
14.7 Manitima transport in bulk according to	
· 14.7 Maritime transport in bulk according to 1	Not applicable.
instruments	ivoi applicable.
	тог иррисиоте.
instruments · Transport/Additional information:	1101 иррисион.
instruments · Transport/Additional information: · ADR	
instruments · Transport/Additional information: · ADR · Limited quantities (LQ)	1L
instruments · Transport/Additional information: · ADR	1L Code: E0
instruments Transport/Additional information: ADR Limited quantities (LQ) Excepted quantities (EQ)	1L
instruments · Transport/Additional information: · ADR · Limited quantities (LQ)	1L Code: E0 Not permitted as Excepted Quantity
instruments Transport/Additional information: ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category	1L Code: E0 Not permitted as Excepted Quantity 2
instruments Transport/Additional information: ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code IMDG	1L Code: E0 Not permitted as Excepted Quantity 2
instruments Transport/Additional information: ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code IMDG Limited quantities (LQ)	1L Code: E0 Not permitted as Excepted Quantity 2 D
instruments Transport/Additional information: ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category Tunnel restriction code IMDG	1L Code: E0 Not permitted as Excepted Quantity 2 D

SECTION 15: Regulatory information

 \cdot 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture VOC: <840g/l

(Contd. on page 10)

Printing date 17.04.2024 Version number 1 Revision: 17.04.2024

Trade name: Aerosol SOLL Spray putty

(Contd. of page 9)

· Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

67-64-1 acetone Listed

· Reportable poisons

None of the ingredients is listed.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- · Technical instructions (air):

Class	Share in %
NK	50-100

- · Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H201 Explosive; mass explosion hazard.
- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H361 Suspected of damaging fertility or the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.
- $EUH018\ In\ use\ may\ form\ flammable/explosive\ vapour-air\ mixture.$
- EUH066 Repeated exposure may cause skin dryness or cracking.
- · Department issuing SDS: Product safety department
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

(Contd. on page 11)

(Contd. of page 10)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.04.2024 Version number 1 Revision: 17.04.2024

Trade name: Aerosol SOLL Spray putty

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values Expl. 1.1: Explosives – Division 1.1

Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols – Category 1

: Aerosols – Category 3

Press. Gas (Comp.): Gases under pressure - Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

* * Data compared to the previous version altered.

GB