

# Safety data sheet

## according to 1907/2006/EC, Article 31 (2020/878)

Printing date: 24.11.2023

Version: 14 (replaces version 13)

Revision: 24.11.2023

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** SOLL Body Cavity Protection, Transparent Aerosol
- **Article number:** S700213
- **UFI:** AJ7E-T07P-700V-QWVJ
- **1.2 Relevant identified uses of the substance or mixture and uses advised against -**
- **Application of the substance / the mixture**  
Metal surface treatment  
Aerosol coating
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
UAB HELVINA  
Parko str. 96, Ramu iai  
LT-54464 Kaunas distr., Lithuania  
Tel: +370 37 308901  
Fax: +370 37 308902  
E-mail: info@helvina.lt
- **1.4 Emergency telephone number:**  
Poison control and information office: Tel.: +370 5 236 2052 or +370 687 53378

### SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Aerosol 1                      H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS09 environment

Aquatic Chronic 2 H411                      Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2                      H315                      Causes skin irritation.

STOT SE 3                      H336                      May cause drowsiness or dizziness.

- **2.2 Label elements**

- **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

- **Hazard pictograms**



GHS02



GHS07



GHS09

- **Signal word** Danger

- **Hazard-determining components of labelling:**

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Hydrocarbons, C9, aromatics

(Contd. on page 2)

DE-EN

# Safety data sheet

## according to 1907/2006/EC, Article 31 (2020/878)

Printing date: 24.11.2023

Version: 14 (replaces version 13)

Revision: 24.11.2023

**Trade name: SOLL Body Cavity Protection, Transparent Aerosol**

(Contd. of page 1)

**Hazard statements**

- H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.  
 H315 Causes skin irritation.  
 H336 May cause drowsiness or dizziness.  
 H411 Toxic to aquatic life with long lasting effects.

**Precautionary statements**

- P101 If medical advice is needed, have product container or label at hand.  
 P102 Keep out of reach of children.  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P211 Do not spray on an open flame or other ignition source.  
 P251 Do not pierce or burn, even after use.  
 P260 Do not breathe mist/vapours/spray.  
 P271 Use only outdoors or in a well-ventilated area.  
 P273 Avoid release to the environment.  
 P280 Wear protective gloves / eye protection.  
 P302+P352 IF ON SKIN: Wash with plenty of soap and water.  
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P403 Store in a well-ventilated place.  
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Additional information:**

Buildup of explosive mixtures possible without sufficient ventilation.

**2.3 Other hazards**
**Results of PBT and vPvB assessment**

- **PBT:** Not applicable.  
 • **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

**3.2 Mixtures**
**Description: -**
**Dangerous components:**

EC number: 921-024-6 Reg.nr.: 01-2119475514-35	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	25-<50%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32	butane (containing < 0.1% butadiene (203-450-8), Note K) Flam. Gas 1A, H220; Press. Gas (Comp.), H280	10-<25%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1A, H220; Press. Gas (Comp.), H280	10-<25%
EC number: 919-857-5 Reg.nr.: 01-2119463258-33	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336, EUH066	10-<25%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27	isobutane (containing < 0,1 % butadiene (203-450-8), Note K) Flam. Gas 1A, H220; Press. Gas (Comp.), H280	2,5-<10%
CAS: 128601-23-0 EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Hydrocarbons, C9, aromatics Consisting of: 98-82-8 isopropylbenzene (<2%); 71-43-2 benzene (<0,1%) Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336, EUH066	1-<2,5%
EC number: 918-481-9 Reg.nr.: 01-2119457273-39	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclic, <2% aromatics. Asp. Tox. 1, H304, EUH066	1-<2,5%

(Contd. on page 3)

# Safety data sheet

## according to 1907/2006/EC, Article 31 (2020/878)

Printing date: 24.11.2023

Version: 14 (replaces version 13)

Revision: 24.11.2023

**Trade name: SOLL Body Cavity Protection, Transparent Aerosol**

(Contd. of page 2)

**Additional information:**

Aerosols and containers fitted with a solid atomizer containing substances or mixtures classified as hazardous by aspiration shall not be labelled for that hazard.

The text of the hazard statements mentioned here can be found in chapter 16.

### SECTION 4: First aid measures

**4.1 Description of first aid measures**

**After inhalation:** In case of unconsciousness place patient stably in side position for transportation.

**After skin contact:** Immediately wash with water and soap and rinse thoroughly.

**After eye contact:** Rinse opened eye for several minutes under running water.

**After swallowing:** Do not induce vomiting; call for medical help immediately.

**4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

### SECTION 5: Firefighting measures

**5.1 Extinguishing media**
**Suitable extinguishing agents:**

Water haze

Fire-extinguishing powder

Carbon dioxide

Alcohol resistant foam

**For safety reasons unsuitable extinguishing agents:** Water with full jet

**5.2 Special hazards arising from the substance or mixture** No further relevant information available.

**5.3 Advice for firefighters**

**Protective equipment:** Mount respiratory protective device.

### SECTION 6: Accidental release measures

**6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

**6.2 Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

**6.3 Methods and material for containment and cleaning up:**

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

**6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### SECTION 7: Handling and storage

**7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.

**Information about fire - and explosion protection:**

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

(Contd. on page 4)

# Safety data sheet

## according to 1907/2006/EC, Article 31 (2020/878)

Printing date: 24.11.2023

Version: 14 (replaces version 13)

Revision: 24.11.2023

**Trade name: SOLL Body Cavity Protection, Transparent Aerosol**

(Contd. of page 3)

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

· **Information about storage in one common storage facility:**

Observe official regulations on storing packagings with pressurised containers.

· **Further information about storage conditions:**

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· **Storage class: 2 B**

· **7.3 Specific end use(s)** No further relevant information available.

\*

### SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

**106-97-8 butane (containing < 0.1% butadiene (203-450-8), Note K)**

AGW (Germany)	Long-term value: 2400 mg/m <sup>3</sup> , 1000 ppm 4(II);DFG
---------------	---

**74-98-6 propane**

AGW (Germany)	Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm 4(II);DFG
---------------	---

**75-28-5 isobutane (containing < 0,1 % butadiene (203-450-8), Note K)**

AGW (Germany)	Long-term value: 2400 mg/m <sup>3</sup> , 1000 ppm 4(II);DFG
---------------	---

**Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclic, <2% aromatics.**

TLV (Germany)	Short-term value: 1200, 184
---------------	-----------------------------

**57-11-4 stearic acid, pure**

MAK (Germany)	vgl. Abschn. IIb und Xc
---------------	-------------------------

**9003-29-6 Polybutene (Isobutylene/butene copolymer)**

MAK (Germany)	vgl. Abschn. IIb und Xc
---------------	-------------------------

· **DNELs**

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane**

Oral	DNEL Long term-systemic	699 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	699 mg/kg bw/day (Consumer) 773 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-systemic	608 mg/m <sup>3</sup> (Consumer) 2035 mg/m <sup>3</sup> (Worker)

**Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics**

Oral	DNEL Long term-systemic	125 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	125 mg/kg bw/day (Consumer) 208 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-systemic	185 mg/m <sup>3</sup> (Consumer) 871 mg/m <sup>3</sup> (Worker)

**128601-23-0 Hydrocarbons, C9, aromatics**

Oral	DNEL Long term-systemic	11 mg/kg bw/day (Consumer)
------	-------------------------	----------------------------

(Contd. on page 5)

DE-EN

# Safety data sheet

## according to 1907/2006/EC, Article 31 (2020/878)

Printing date: 24.11.2023

Version: 14 (replaces version 13)

Revision: 24.11.2023

**Trade name: SOLL Body Cavity Protection, Transparent Aerosol**

(Contd. of page 4)

Dermal	DNEL Long term-systemic	11 mg/kg bw/day (Consumer) 25 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-systemic	32 mg/m <sup>3</sup> (Consumer) 100 mg/m <sup>3</sup> (Worker)

· **Additional information:** The lists valid during the making were used as basis.

### · 8.2 Exposure controls

· **Appropriate engineering controls** No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

General ventilation

· **Respiratory protection:**

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A2/P2

· **Hand protection**



Protective gloves

Solvent resistant gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

Recommended thickness of the material:  $\geq 0,5$  mm

· **Penetration time of glove material**

For continuous contact we recommend gloves with breakthrough time of at least 240 minutes, with the preference given to a breakthrough time greater than 480 minutes. For short-term or splash guard we recommend the same. We are aware that suitable gloves that offer this level of protection may not be available.

In that case, a shorter breakthrough time are acceptable as long as the procedures governing maintenance and timely replacement are followed. The thickness of the gloves is not a good measure of the resistance of the gloves against a chemical substance, because this depends on the exact composition of the material from which the gloves are made.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye/face protection**

Safety glasses



Tightly sealed goggles

· **Body protection:**

Use protective suit. (EN-13034/6)

Fully skin-covering anti-static, chemical- and oil-resistant clothing and safety shoes are recommended.

(EN1149; EN340&EN ISO 13688; EN13034-6).

(Contd. on page 6)

DE-EN

# Safety data sheet

## according to 1907/2006/EC, Article 31 (2020/878)

Printing date: 24.11.2023

Version: 14 (replaces version 13)

Revision: 24.11.2023

Trade name: SOLL Body Cavity Protection, Transparent Aerosol

(Contd. of page 5)

· **Environmental exposure controls** Use an appropriate container to avoid environmental pollution.

### SECTION 9: Physical and chemical properties

#### · 9.1 Information on basic physical and chemical properties

##### · General Information

· Physical state	Aerosol
· Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
· Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and boiling range	-44,5 °C
· Flammability	Not applicable.
· Lower and upper explosion limit	
· Lower:	0,5 Vol %
· Upper:	10,9 Vol %
· Flash point:	-97 °C
· Ignition Temperature	>200 °C
· pH	Mixture is non-polar/aprotic.
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic:	Not determined
· Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure at 20 °C:	3800 hPa
· Vapor Pressure at 50 °C:	6500 hPa
· Density and/or relative density	
· Density at 20 °C:	~0,667 g/cm <sup>3</sup>
· Relative density	Not determined.
· Vapour density	Not determined.

#### · 9.2 Other information

· Form:	Aerosol
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Organic solvents:	88,0 %
· Solids content:	5,9 %
· Evaporation rate	Not applicable.

#### · Information with regard to physical hazard classes

· Explosives	Void
· Flammable gases	Void
· Aerosols	Extremely flammable aerosol. Pressurised container: May burst if heated.
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void

(Contd. on page 7)

DE-EN

# Safety data sheet

## according to 1907/2006/EC, Article 31 (2020/878)

Printing date: 24.11.2023

Version: 14 (replaces version 13)

Revision: 24.11.2023

**Trade name: SOLL Body Cavity Protection, Transparent Aerosol**

(Contd. of page 6)

- |   |      |
|---|------|
| · Substances and mixtures, which emit flammable gases in contact with water | Void |
| · Oxidising liquids   | Void |
| · Oxidising solids  | Void |
| · Organic peroxides   | Void |
| · Corrosive to metals   | Void |
| · Desensitised explosives   | Void |

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

#### · LD/LC50 values relevant for classification:

##### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Oral	LD50	>5840 mg/kg (Rat)
Dermal	LD50	>2920 mg/kg (Rabbit)
Inhalative	LC50 (4h)	>25 mg/l (Rat)

##### Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Oral	LD50	>5000 mg/kg (Rat) (Acute Oral Toxicity)
Dermal	LD50	3160 mg/kg (Rabbit) (Acute Dermal Toxicity)
Inhalative	LC50 (4h)	>4951 mg/l (Rat)
	LC50 (4h)	4951 mg/m3 (Rat)

##### 128601-23-0 Hydrocarbons, C9, aromatics

Oral	LD50	3492 mg/kg (Rat)
Dermal	LD50	>3160 mg/kg (Rabbit)
Inhalative	LC50 (4h)	>6193 mg/l (Rat) (Acute Inhalation Toxicity)

##### Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclic, <2% aromatics.

Oral	LD50	>5000 mg/kg (Rat)
Dermal	LD50	>2000 mg/kg (Rabbit)
Inhalative	LC50 (4h)	4951 mg/l (Rat)

- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

(Contd. on page 8)

# Safety data sheet

## according to 1907/2006/EC, Article 31 (2020/878)

Printing date: 24.11.2023

Version: 14 (replaces version 13)

Revision: 24.11.2023

**Trade name: SOLL Body Cavity Protection, Transparent Aerosol**

(Contd. of page 7)

**· 11.2 Information on other hazards**
**· Endocrine disrupting properties**

None of the ingredients is listed.

**SECTION 12: Ecological information**
**· 12.1 Toxicity**
**· Aquatic toxicity:**
**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane**

NOELR (72h)	3 mg/l (Pseudokirchneriella subcapitata)
EL50 (48h)	3 mg/l (Daphnia magna)
EL50 (72h)	30-100 mg/l (Pseudokirchneriella subcapitata)
LL50 (96h)	11,4 mg/l (Oncorhynchus mykiss)
NOEC (21 days)	0,17 mg/l (Daphnia magna)
LOEC (21 days)	0,32 mg/l (Daphnia magna)

**Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics**

EL0 (48h)	1000 mg/l (Daphnia magna)
NOELR (72h)	100 mg/l (Pseudokirchneriella subcapitata)
EL50 (72h)	>1000 mg/l (Pseudokirchneriella subcapitata)
LL50 (96h)	>1000 mg/l (Onc)

**128601-23-0 Hydrocarbons, C9, aromatics**

NOELR (72h)	1 mg/l (Pseudokirchneriella subcapitata)
EL50 (48h)	3,2 mg/l (Daphnia magna)
LL50 (96h)	9,2 mg/l (Oncorhynchus mykiss)

**Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclic, <2% aromatics.**

EL0 (48h)	1000 mg/l (Daphnia magna)
EL0 (72h)	1000 mg/l (Pseudokirchneriella subcapitata)
LL0 (96h)	1000 mg/l (Oncorhynchus mykiss)

**· 12.2 Persistence and degradability** Not easily biodegradable

**· 12.3 Bioaccumulative potential** No further relevant information available.

**· 12.4 Mobility in soil** No further relevant information available.

**· 12.5 Results of PBT and vPvB assessment**
**· PBT:** Not applicable.

**· vPvB:** Not applicable.

**· 12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

**· 12.7 Other adverse effects**
**· Remark:** Toxic for fish

**· Additional ecological information:**
**· General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

DE-EN

(Contd. on page 9)

# Safety data sheet

according to 1907/2006/EC, Article 31 (2020/878)

Printing date: 24.11.2023

Version: 14 (replaces version 13)

Revision: 24.11.2023

Trade name: SOLL Body Cavity Protection, Transparent Aerosol

(Contd. of page 8)

## SECTION 13: Disposal considerations

### · 13.1 Waste treatment methods

#### · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

#### · European waste catalogue

08 02 99	wastes not otherwise specified
HP3	Flammable
HP4	Irritant - skin irritation and eye damage
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP14	Ecotoxic

#### · Uncleaned packaging:

· **Recommendation:** Disposal must be made according to official regulations.

## SECTION 14: Transport information

### · 14.1 UN number or ID number

#### · ADR, ADN, IMDG, IATA

UN1950

### · 14.2 UN proper shipping name

#### · ADR, ADN

UN1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS

#### · IMDG

AEROSOLS, MARINE POLLUTANT

#### · IATA

AEROSOLS, flammable

### · 14.3 Transport hazard class(es)

#### · ADR



#### · Class

2 5F Gases.

#### · Label

2.1

#### · ADN

#### · ADN/R Class:

2 5F

#### · IMDG



#### · Class

2.1 Gases.

#### · Label

2.1

#### · IATA



#### · Class

2.1 Gases.

#### · Label

2.1

(Contd. on page 10)

DE-EN

# Safety data sheet

## according to 1907/2006/EC, Article 31 (2020/878)

Printing date: 24.11.2023

Version: 14 (replaces version 13)

Revision: 24.11.2023

**Trade name: SOLL Body Cavity Protection, Transparent Aerosol**

(Contd. of page 9)

· <b>14.4 Packing group</b> · <b>ADR, IMDG, IATA</b>	Void
· <b>14.5 Environmental hazards:</b>  · <b>Marine pollutant:</b> · <b>Special marking (ADR):</b>	Product contains environmentally hazardous substances: Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane Symbol (fish and tree) Symbol (fish and tree)
· <b>14.6 Special precautions for user</b> · <b>Hazard identification number (Kemler code):</b> · <b>EMS Number:</b> · <b>Stowage Code</b>  · <b>Segregation Code</b>	Warning: Gases. - F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· <b>14.7 Maritime transport in bulk according to IMO instruments</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>ADR</b> · <b>Excepted quantities (EQ)</b>  · <b>Transport category</b> · <b>Tunnel restriction code</b>	Code: E0 Not permitted as Excepted Quantity 2 D
· <b>IMDG</b> · <b>Limited quantities (LQ)</b> · <b>Excepted quantities (EQ)</b>	1L Code: E0 Not permitted as Excepted Quantity
· <b>UN "Model Regulation":</b>	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

\*

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category**  
P3a FLAMMABLE AEROSOLS  
E2 Hazardous to the Aquatic Environment
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

(Contd. on page 11)

DE-EN

# Safety data sheet

## according to 1907/2006/EC, Article 31 (2020/878)

Printing date: 24.11.2023

Version: 14 (replaces version 13)

Revision: 24.11.2023

**Trade name: SOLL Body Cavity Protection, Transparent Aerosol**

(Contd. of page 10)

· **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

· **REGULATION (EU) 2019/1148**

· **Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

· **Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

None of the ingredients is listed.

· **Regulation (EC) No 273/2004 on drug precursors**

None of the ingredients is listed.

· **Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors**

None of the ingredients is listed.

· **National regulations:**

· **Technical instructions (air):**

Class	Share in %
NK	75-<100

· **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.

· **VOC-CH** 88,03 %

· **VOC-EU** ~587,2 g/l

· **Danish MAL Code** 4-3

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

· **Classification according to Regulation (EC) No 1272/2008**

Physical and chemical properties: The classification is based on the results of the mixtures tested. Health hazards, Environmental hazards: The method of classification of mixtures based on the constituents of the mixture (sum formula).

· **Contact:** info@helvina.lt

· **Date of previous version:** 21.11.2023

· **Version number of previous version:** 13

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances

(Contd. on page 12)

# Safety data sheet

## according to 1907/2006/EC, Article 31 (2020/878)

Printing date: 24.11.2023

Version: 14 (replaces version 13)

Revision: 24.11.2023

**Trade name: SOLL Body Cavity Protection, Transparent Aerosol**

(Contd. of page 11)

CAS: Chemical Abstracts Service (division of the American Chemical Society)

GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)

MAL-Code: Måleteknisk Arbejdshygienisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

DE-EN