Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.03.2023 *Version number 70 (replaces version 69)* Revision: 30.03.2023 SECTION 1: Identification of the substance/mixture and of the company/undertaking · 1.1 Product identifier • Trade name: SOLL SF4 HS Acrylfiller 4+1 · 1.2 Relevant identified uses of the substance or mixture and uses advised against · Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) • Product category PC9b Fillers, putties, plasters, modelling clay · Application of the substance / the mixture Filler • 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: UAB "Helvina" Parko str. 96 LT-54464 Ramučiai, Kaunas district Lithuania Tel.:+37037308901 Fax. +37037308902 e-mail info@helvina.lt • 1.4 Emergency telephone number: Poison control and information office: Tel.: +370 5 236 2052 or +370 687 53378 **SECTION 2: Hazards identification** · 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008 flame Flam. Liq. 3 H226 Flammable liquid and vapour. environment Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects. · 2.2 Label elements · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation. · Hazard pictograms GHS02 GHS09 · Signal word Warning · Hazard statements H226 Flammable liquid and vapour. H411 Toxic to aquatic life with long lasting effects. · Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 Keep container tightly closed. P242 Use non-sparking tools. P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. (Contd. on page 2)

GB

Printing date 30.03.2023

Version number 70 (replaces version 69)

Revision: 30.03.2023

Trade name: SOLL SF4 HS Acrylfiller 4+1

(Contd. of page 1)

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P403+P235 Store in a well-ventilated place. Keep cool.

• Additional information:

EUH208 Contains 2,3-Epoxypropyl neodecanoate. May produce an allergic reaction.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-Butyl acetate	≤20%
CAS: 7779-90-0 EINECS: 231-944-3 Reg.nr.: 01-2119485044-40	<i>Trizinc bis(orthophosphate)</i> Aquatic Acute 1, H400; Aquatic Chronic 1, H410	2.5-<10%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-Methoxy-1-methylethyl acetate Flam. Liq. 3, H226; 🔶 STOT SE 3, H336	<2.5%
CAS: 64742-95-6 EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Hydrocarbons, C9, aromatics Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336, EUH066	1-<2.5%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	Xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	1-<2.5%
CAS: 1314-13-2 EINECS: 215-222-5 Reg.nr.: 01-2119463881-32	zinc oxide Aquatic Acute 1, H400; Aquatic Chronic 1, H410	<i>≥</i> 0.025-<0.25%
CAS: 26761-45-5 EINECS: 247-979-2 Reg.nr.: 01-2119431597-33	2,3-Epoxypropyl neodecanoate Muta. 2, H341; Aquatic Chronic 2, H411; Skin Sens. 1, H317	≥0.1-<0.25%
• Additional information: For	the wording of the listed hazard phrases refer to section 16.	

SECTION 4: First aid measures

• 4.1 Description of first aid measures

• General information: Immediately remove any clothing soiled by the product.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately rinse with water.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

• After swallowing: If symptoms persist consult doctor.

• 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3) GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.03.2023

Version number 70 (replaces version 69)

Revision: 30.03.2023

Trade name: SOLL SF4 HS Acrylfiller 4+1

• 4.3 Indication of any immediate medical attention and special treatment needed

(Contd. of page 2)

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

- · 6.2 Environmental precautions:
- Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling Use only in well ventilated areas.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep container tightly sealed.
- Storage class: 3
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

123-86-4 n-Butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm

Long-term value: 724 mg/m³, 150 ppm

(Contd. on page 4)

GB

Printing date 30.03.2023

Version number 70 (replaces version 69)

Revision: 30.03.2023

(Contd. of page 3)

Trade name: SOLL SF4 HS Acrylfiller 4+1

	55-6 2-Methoxy-1-methylethyl acetate
WEL	Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk

1330-20-7 Xylene

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV

· Ingredients with biological limit values:

1330-20-7 Xylene

BMGV 650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid

• Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:
- Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.
- Respiratory protection: Filter A/P2 (EN 141, EN 143)
- · Hand protection



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.7 *mm*

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Breakthrough time of glove material Value for the permeation: Level ≤ 3
- Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties
- · General Information
- · Physical state Fluid · Colour: According to product specification · Odour: Characteristic · Odour threshold: Not determined.

(Contd. on page 5)

GB

Printing date 30.03.2023

Version number 70 (replaces version 69)

Revision: 30.03.2023

Trade name: SOLL SF4 HS Acrylfiller 4+1

	(Contd. of page
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling	
range	124-128 °C (123-86-4 n-Butyl acetate)
Flammability	Flammable.
Lower and upper explosion limit	
Lower:	1.2 Vol %
Upper:	7.5 Vol %
Flash point:	27 °C (DIN 53213)
Auto-ignition temperature:	370 °C (DIN 51794)
Decomposition temperature:	Not determined.
pH	Not determined.
Viscosity:	
Kinematic viscosity at 20 °C	70-80 s (ISO 6 mm)
Dynamic:	Not determined.
Solubility	
water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure at 20 °C:	10.7 hPa
Density and/or relative density	
Density at 20 °C:	1.66 g/cm ³ (DIN 53217)
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Fluid
Important information on protection of health an	
environment, and on safety.	
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation
	explosive air/vapour mixtures are possible.
Solvent content:	1 1 1
VOC (EC)	21.19 %
Solids content (weight-%):	78.8 %
Change in condition	
Evaporation rate	Not determined.
Information with regard to physical hazard classe	25
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Flammable liquid and vapour.
Flammable solids	Void
	Void
Self-reactive substances and mixtures	
Self-reactive substances and mixtures Pyrophoric liquids	Void
Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids	Void Void
Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures	Void
Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammable	Void Void Void
Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water	Void Void Void Void
Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water Oxidising liquids	Void Void Void Void Void
Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water Oxidising liquids Oxidising solids	Void Void Void Void Void Void
Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water Oxidising liquids Oxidising solids Organic peroxides	Void Void Void Void Void Void Void
Self-reactive substances and mixtures Pyrophoric liquids Pyrophoric solids Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water	Void Void Void Void Void Void

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.03.2023

Version number 70 (replaces version 69)

Revision: 30.03.2023

(Contd. of page 5)

Trade name: SOLL SF4 HS Acrylfiller 4+1

· Desensitised explosives

Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions No dangerous reactions known.

• 10.4 Conditions to avoid No further relevant information available.

• 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

• Acute toxicity Based on available data, the classification criteria are not met.

- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

• Germ cell mutagenicity Based on available data, the classification criteria are not met.

· Carcinogenicity Based on available data, the classification criteria are not met.

 $\cdot \textit{Reproductive toxicity Based on available data, the classification criteria are not met.}$

- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.

• Aspiration hazard Based on available data, the classification criteria are not met.

• 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

- Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- **Remark:** Toxic for fish
- Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) : hazardous for water

Do not allow product to reach ground water, water course or sewage system.

- Danger to drinking water if even small quantities leak into the ground.
- Also poisonous for fish and plankton in water bodies.

(Contd. on page 7)

Printing date 30.03.2023

Version number 70 (replaces version 69)

Revision: 30.03.2023

Trade name: SOLL SF4 HS Acrylfiller 4+1

Toxic for aquatic organisms

SECTION 13: Disposal considerations

• 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

• 14.1 UN number or ID number • ADR, IMDG, IATA	UN1263
· 14.2 UN proper shipping name	
ADR	UN1263 PAINT, MARINE POLLUTANT
IMDG	ENVIRONMENTALLY HAZARDOUS PAINT (Trizinc bis(orthophosphate), Solvent naphtha, MARINE POLLUTANT
· IATA	PAINT
14.3 Transport hazard class(es)	
ADR	
· Class	3 (F1) Flammable liquids.
Label	3
· Class	3 Flammable liquids.
· Label	3
· Class	3 Flammable liquids.
Label	3
· 14.4 Packing group · ADR, IMDG, IATA	111
14.5 Environmental hazards:	Product contains environmentally hazardous substances
14.5 Environmental nazaras:	Epoxyde resin
Marine pollutant:	Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)

(Contd. of page 6)

Printing date 30.03.2023

Version number 70 (replaces version 69)

Revision: 30.03.2023

Trade name: SOLL SF4 HS Acrylfiller 4+1

	(Contd. of page
· 14.6 Special precautions for user	Warning: Flammable liquids.
· Hazard identification number (Kemler code):	30
EMS Number:	<i>F-E,<u>S-E</u></i>
Stowage Category	A
14.7 Maritime transport in bulk according to IM	10
instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Transport category	3
Tunnel restriction code	D/E
Remarks:	$\leq 5 l: 2.2.3.1.5 ADR$
IMDG	
Limited quantities (LQ)	5L
Remarks:	≤ 5 l: 2.2.3.1.5 IMDG
UN "Model Regulation":	UN 1263 PAINT, 3, III, MARINE POLLUTANT ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category
- E2 Hazardous to the Aquatic Environment
- P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

· National regulations:

• Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %
NK	10-25

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H341 Suspected of causing genetic defects.

(Contd. on page 9)

Printing date 30.03.2023

Safety data sheet according to 1907/2006/EC, Article 31

according to 1907/2006/EC, Article 31 Version number 70 (replaces version 69)

Revision: 30.03.2023

Trade name: SOLL SF4 HS Acrylfiller 4+1

	(Contd. of page
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH06	6 Repeated exposure may cause skin dryness or cracking.
	ication according to Regulation (EC) No 1272/2008
	ssification of the mixture is generally based on the calculation method using substance data accordin
	lation (EC) No 1272/2008.
Abbrevi	iations and acronyms:
RID: Règ	lement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning th
	onal Transport of Dangerous Goods by Rail)
	ternational Civil Aviation Organisation
	cord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning th
	onal Carriage of Dangerous Goods by Road)
	ternational Maritime Code for Dangerous Goods
	ernational Air Transport Association
	bally Harmonised System of Classification and Labelling of Chemicals
	European Inventory of Existing Commercial Chemical Substances European List of Notified Chemical Substances
	emical Abstracts Service (division of the American Chemical Society)
	latile Organic Compounds (USA, EU)
	sistent, Bioaccumulative and Toxic
	ry Persistent and very Bioaccumulative
	. 3: Flammable liquids – Category 3
	x. 4: Acute toxicity – Category 4
Skin Irrit.	2: Skin corrosion/irritation – Category 2
	2: Serious eye damage/eye irritation – Category 2
	1: Skin sensitisation – Category 1
	Germ cell mutagenicity – Category 2
	3: Specific target organ toxicity (single exposure) – Category 3
	2: Specific target organ toxicity (repeated exposure) – Category 2
	1: Aspiration hazard – Category 1
	<i>Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1</i>
	Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
	Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
" Data (compared to the previous version altered.